




42CT FANCOIL UNIT

Project:		Country:	
Customer:		City:	
Reference:		Date:	30.12.2021 12:16:30

Model	42CT0230S1SPRR1LN0				Ref No		
Performance Data		Cooling (Season 1)			Heating (Season 2)		
		High	Medium	Low	High	Medium	Low
Total Capacity	kW	2.58	2.02	0.92	5.74	4.54	2.07
Sensible Capacity	kW	1.66	1.28	0.56			
Air Side Data							
Room Dry / Wet Bulb Temp.	°C	27.00 / 19.53			20.00 / 13.78		
Room Humidity	%	50.00			50.00		
Air Outlet Temperature	°C	13.86	13.23	11.42	63.89	66.90	73.85
Air Outlet Humidity	%	93.55	95.10	98.34	4.77	4.16	3.07
Room ΔT Factor	K	1.00					
Fluid Side Data							
Fluid / Mixture Rate	- / %	Water / 0			Water / 0		
Inlet / Outlet Temperature	°C	7.0 / 12.0	7.0 / 12.0	7.0 / 12.0	80.0 / 60.0	80.0 / 60.0	80.0 / 60.0
Fluid Volumetric Flow	m³/h	0.45	0.35	0.16	0.26	0.20	0.09
Fluid Mass Flow	kg/s	0.12	0.10	0.05	0.07	0.05	0.02
Fluid Pressure Drop	kPa	30.85	20.75	6.84	8.73	6.35	2.70
Condensated Water	kg/h	1.16	0.94	0.47			
Fan / Efficiency Data							
Air Flow	m³/h	389.60	288.45	113.94			
External Static Pressure	Pa	30	30	30			
Total Fan Power Input	Watt	48.53	39.76	28.51			
Total Fan Current	A	0.21	0.17	0.12			
Fan Specific Power	W/l/s	0.45	0.5	0.9			
Sound Power Level (LWA)	dBA	53.70	49.38	33.00			
Sound Pressure Level (LPA)	dBA	43.70	39.38	23.00			
Ceiling / Room Attenuation	dBA	5 / 5					
Voltage / Frequency / Phase	V/Hz/Ph	230 / 50 / 1					
Efficiency Class	-	-			-		
FCEER / FCCOP	-	0			0		
Product Data							
Product Series	-	Concealed Ceiling Horizontal		Drain Pan	Standard		
Type of Pipe / Coil Rows	-	2 / 3		Plenum	Rear Return		
Casing	-	Galvanized Steel		Filter	Standard		
Coil Tube / Fin Material	-	Copper / Hydrophilic Alu.		Fresh Air	None		
				W (mm)	703	Din (-)	3/4"
				H (mm)	250	Dout (-)	3/4"
				L (mm)	540	Drain (-)	3/4"
				Weight (kg)	12.10		

ALARKO CARRIER FANCOIL PROSECTOR SOFTWARE / V 1.0 / 01.09.2021

ALARKO CARRIER / +90 262 648 60 00 / info@alarko-carrier.com.tr / www.alarko-carrier.com.tr